



UNITED STATES WELDING CORPORATION

<p align="center">USW ALLOY DESIGNATION AND DESCRIPTION</p>	<p align="center">TURBALOY® 13-8 Mo HQ-GRADE GTAW SOLID BARE WELDING WIRE IRON BASE</p>	<p align="center">ISO 9001 AS 9100</p>	<p align="center">DATA SHEET 5840</p>																																																	
<p align="center">CROSS-REFERENCE CONFORMANCE SPECIFICATIONS</p>	<p>AMS 5840 UNS S13889 PH13-8 Mo</p> <p align="right">13Cr 8Ni 2.3Mo 1.1Al (XM - 13) Available in MC-GRADE</p>																																																			
<p align="center">METALLURGICAL BACKGROUND INFORMATION</p>	<p>TURBALOY® 13-8 wire is manufactured by special lubricant-free, roller-die forming followed by surface abrasion and cleaning processes. This manufacturing route ensures consistent metallurgical integrity of the alloy with regard to control of trace elements and physical purity of the welding wire surface.</p> <p>TURBALOY® 13-8 is a martensitic, precipitation hardening stainless engineering alloy giving high strength and corrosion resistance. The high purity and controlled composition of this filler metal enables matching base alloys to be welded under more restraint and in thicker cross section and still obtain good transverse toughness. Low carbon minimizes grain boundary carbide formation.</p>																																																			
<p align="center">MATERIALS TO BE WELDED AND APPLICATIONS</p>	<p>ASTM A564, A693, A705, (XM - 13 grade). UNS 13800 UNS S13800, PH13 - 8 Mo. AMS629, 5412, 5864.</p> <p>Aircraft components and fittings. Can be used as-welded: PWHT will optimize properties. The aluminum content needs to be carefully protected by using adequate pure argon gas shielding.</p>																																																			
<p align="center">WIRE CHEMISTRY WT%</p>	<table border="0"> <tr> <td>Carbon</td><td>-</td><td>0.05</td><td>Molybdenum</td><td>2.00</td><td>2.50</td><td></td></tr> <tr> <td>Manganese</td><td>-</td><td>0.10</td><td>Aluminum</td><td>0.90</td><td>1.35</td><td></td></tr> <tr> <td>Silicon</td><td>-</td><td>0.10</td><td>Nitrogen</td><td>-</td><td>0.01</td><td>(100ppm)</td></tr> <tr> <td>Sulfur</td><td>-</td><td>0.010</td><td>Oxygen</td><td>-</td><td>0.005</td><td>(50ppm)</td></tr> <tr> <td>Phosphorus</td><td>-</td><td>0.008</td><td>Hydrogen</td><td>-</td><td>0.0025</td><td>(25ppm)</td></tr> <tr> <td>Chromium</td><td>12.25</td><td>13.25</td><td>Iron</td><td></td><td></td><td>Balance</td></tr> <tr> <td>Nickel</td><td>7.50</td><td>8.50</td><td></td><td></td><td></td><td></td></tr> </table>			Carbon	-	0.05	Molybdenum	2.00	2.50		Manganese	-	0.10	Aluminum	0.90	1.35		Silicon	-	0.10	Nitrogen	-	0.01	(100ppm)	Sulfur	-	0.010	Oxygen	-	0.005	(50ppm)	Phosphorus	-	0.008	Hydrogen	-	0.0025	(25ppm)	Chromium	12.25	13.25	Iron			Balance	Nickel	7.50	8.50				
Carbon	-	0.05	Molybdenum	2.00	2.50																																															
Manganese	-	0.10	Aluminum	0.90	1.35																																															
Silicon	-	0.10	Nitrogen	-	0.01	(100ppm)																																														
Sulfur	-	0.010	Oxygen	-	0.005	(50ppm)																																														
Phosphorus	-	0.008	Hydrogen	-	0.0025	(25ppm)																																														
Chromium	12.25	13.25	Iron			Balance																																														
Nickel	7.50	8.50																																																		
<p align="center">WELD PROPERTIES</p>	<p>Peak hardness of base metal: 500 HV Solution treated material: 300HV</p> <p align="right">Density: 7.82gm/cc</p>																																																			
<p align="center">SIZES AND FORMS AVAILABLE</p>	<table border="0"> <tr> <td align="center" colspan="2">STRAIGHT LENGTHS</td> <td align="center" colspan="2">SPOOLED WIRE</td> </tr> <tr> <td>5 lb. (2.2kg) packs</td> <td></td> <td>Precision layer wound, with controlled cast and helix</td> <td></td> </tr> <tr> <td>36" (914mm) lengths</td> <td></td> <td>12" (300mm) diameter spools standard</td> <td></td> </tr> <tr> <td>Flag tagged for traceability.</td> <td></td> <td>8" (200mm), 4" (100mm) and proprietary spool sizes</td> <td></td> </tr> <tr> <td>(Double tagging and other lengths on request)</td> <td></td> <td>on request.</td> <td></td> </tr> <tr> <td>Wide range of diameters.</td> <td></td> <td>Wide range of diameters and spool weights.</td> <td></td> </tr> </table>			STRAIGHT LENGTHS		SPOOLED WIRE		5 lb. (2.2kg) packs		Precision layer wound, with controlled cast and helix		36" (914mm) lengths		12" (300mm) diameter spools standard		Flag tagged for traceability.		8" (200mm), 4" (100mm) and proprietary spool sizes		(Double tagging and other lengths on request)		on request.		Wide range of diameters.		Wide range of diameters and spool weights.																										
STRAIGHT LENGTHS		SPOOLED WIRE																																																		
5 lb. (2.2kg) packs		Precision layer wound, with controlled cast and helix																																																		
36" (914mm) lengths		12" (300mm) diameter spools standard																																																		
Flag tagged for traceability.		8" (200mm), 4" (100mm) and proprietary spool sizes																																																		
(Double tagging and other lengths on request)		on request.																																																		
Wide range of diameters.		Wide range of diameters and spool weights.																																																		
<p align="center">PACKAGING</p>	<p>Sealed, air-evacuated, argon purged Vapor Barrier envelopes with desiccants ensure full protection from atmospheric contamination and prolonged shelf-life.</p>																																																			
<p>DFARS Compliant</p>		<p align="right">www.usweldingcorp.com</p>																																																		